SAFETY DATA SHEET Kolor Kut Gasoline Gauging Paste®

SDS-Format GHS Language English (US) WHMIS OSHA HCS 2012

PRODUCT AND COMPANY IDENTIFICATION

Product Name:

KOLR KUT GASOLINE GAUGING PASTED

Code:

KKGGP

Chemical Name:

Not Applicable - Mixture

CAS#

1,

Mixture

Manufacturer/Supplier:

KOLOR KUTO PRODCUTS CO. LTD

Address/Physical:

7915 EAST ELM ST.

HOUSTON,TX 77012 (U.S.A.) P.O.BOX 5415

Mailing:

HOUSTON,TX 77262-5415 (U.S.A.)

Phone Number:

(713) 926-4780

Fax Number:

(713) 928-9025

Emergency Phone Number:

(713) 926-4780

E-Mail:

Uses

Top level indicator paste for Petroleum Products....

Manufactured/Country of Origin

USA

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Component Name

CAS#

% by Weight

OSHA PEL

ACGIH TLV

No Hazardous Ingredients (29 CFR 1910.1200)

 No toxic chemicals subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372 are present.

Special Note: SDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under normal conditions of use, so long as recommended safety precautions are practiced.

3. HAZARDS IDENTIFICATION

Eye Contact: May cause redness and mild discomfort.

Skin Contact: May remove oils from skin with prolonged exposure.

Skin Absorption: Not absorbed through intact skin.

Inhalation: Not a route of entry.

Ingestion: Ingesting large amounts may cause gastrointestinal irritation.

Sensitization: Not a sensitizer.

Chronic Effects: May cause dermatitis in individuals with pre-existing skin disorders. Carcinogenic Effects: No ingredients listed as carcinogenic by IARC, OSHA or NTP.

Mutagenic Effects: No data. Teratogenic Effects: No data. Reproductive Effects: No data.

Kolor Kut Gasoline Gauging Paste - PAGE 1 OF 4

4. FIRST AID MEASURES

Flush eyes with clean water for at least 15 minutes. If irritation occurs, call a physician. Remove any contaminated clothing and wash skin with soap and water. If irritation occurs, call a Physician.

Accidental high pressure injection under skin requires immediate medical attention.

Inhalation: Not applicable to this product.....

Ingestion: Do not induce vomiting and give large quantities of water. Get medical attention if nausea or stomach pains occur.

5. FIRE & EXPLOSION HAZARDS

Flash Point (Method):

Auto-Ignition Temp: Flammable limits in Air:

Combustion Products: Explosion Hazards:

Fire Fighting Measures:

365 Deg F. (185 Deg C.) (COC)

N/A

LEL: N/A

Smoke, Fumes, Carbon Monoxide.

In the presence of mechanical impact or static

discharge: no explosion risk

Use foam, CO2, dry chemical, water fog. Water

can be used to keep containers cool and to flush spills away from fire exposure. Fire Fighters must wear self-contained breathing apparatus in enclosed

areas

6. ACCIDENTAL RELEASE MEASURES

Small Spill: Recover free product. Add sand, earth or some other suitable absorbent. Dispose of material in accordance with all local, state & federal regulations.

Large Spill: Take care to keep product out of sewers and watercourses by diking or impounding, advise authorities if product has entered sewers, watercourses or extensive land areas.

7. HANDLING/STORAGE

Storage

Store in cool, dry area in original or equivalent container in accordance with all applicable regulations. Do not expose to extreme heat or flame.

Store below 150 deg. F. Do not freeze for

preservation of product only.

Handling

Wash thoroughly after handling. Do not get in eyes. follow good hygiene and housekeeping practices. Use

in ventilated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use with adequate ventilation.

Personal Protection: Safety glasses are recommended. Oil impervious gloves for prolonged or Repeated skin contact.

Kolor Kut Gasoline Gauging Paste - PAGE 2 OF 4

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance & Odor

Light Pink Semi-Solid, Slight Odor

PH

Not Applicable

Boiling Point

212 Deg. F

Melting point

120 Deg. F

Specific Gravity (H2O=1)

1 No Data

Water/Oil Distribution Coefficient

N/A

Vapor pressure

Vapor Density (Air=1)

.1

Odor Threshold

<1 No Data

Evaporation Rate

<1 (Ether=1)

Solubility in Water

Yes

10. STABILITY / REACTIVITY

Stability

Stable

Conditions to Avoid

Extreme Heat

Incompatibilities

Strong oxidizers, acids

Hazardous Decomposition Products

Carbon Monoxide, Smoke, Fumes

11. TOXICOLOGICAL INFORMATION

Routes of Entry: Eye, Skin, Ingestion

Toxicological Data:

No Data

12. **ECOLOGICAL INFORMATION**

ECO Toxicity:

No Data

BOD5 & COD:

No Data

Biodegradation Products & Toxicity:

No Data

13. DISPOSAL CONSIDERATIONS

Waste information: Dispose of waste according to federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

Not Regulated

IMO

Not Regulated

IATA

Not Regulated

Kolor Kut Gasoline Gauging Paste - PAGE 3 OF 4

15. REGULATORY INFORMATION

Hazardous Material Information System (HMIS) - USA

Health 0
Fire 1
Reactivity 0
Personal Protection B

SARA Section 313: No ingredients subject to reporting requirements.

TSCA Inventory: All ingredients are listed or exempt.

California Prop. 65: No Ingredients listed. Canada DSL: All ingredients listed. WHMIS Classification: Not controlled.

WHMIS: This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information

16. OTHER INFORMATION

Preparation/Revision Date: 6/23/16 Prepared By: D. Frauenberger

For More information Call: 713-926-4780 HS-Tariff Classification Number: 3403190000

ECCN Number: EAR99-NLR

KOLOR KUT® IS A REGISTERED TRADEMARK OF KOLOR KUT PRODUCTS CO.

HOUSTON, TEXAS USA

Important Notice: Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use & suitability of this product for particular uses are beyond our control. Users should make their own investigation to determine the suitability of the information or products for their respective purposes.